

Ероху 314™

RESIN CURING AGENT - YELLOW

MATERIAL SAFETY DATA SHEET - MSDS

1. IDENTIFICATION OF THE SUBSTANCE

TRADE NAME: Epoxy 314™ Resin Curing Agent - Yellow.

DESCRIPTION: Resin – yellow is based on pure liquid epoxy polymers and polyamine property resins modified

with an organic sulfur complex curing agent. reinforcing seal coating

RECOMMENDED USE: Coating component

SUPPLIER INFORMATION: TECNOLOGIA TOTAL LLC INTTECH PETROL

 8163 Landfall Ct
 1833 Parkridge Dr.

 Gainesville VA 20155, USA
 Norman, OK 73071, USA.

 Tel. +1-561-812-9603
 Tel. +1-405-618-1237

 $\underline{sales@tecnologiatotal.net} \\ \underline{rcastillo@inttechpetrol.com}$

2. HAZARDS IDENTIFICATION

Does not contain resinous carcinogens

3. COMPOSITION

| COMPONENT | Nº CAS | CONTENTS %w/w | HAZARD DATA |
|---|--------------|---------------|----------------------|
| Mercaptan Polymer (Trade Secret) | Trade Secret | <50 | PEL: Not Established |
| | | | TLV: Not Established |
| 2,4,6-tri (dimethylaminomethyl)phenol | 90-72-2 | <7 | TWA: 5ppm 8hr |
| Benzil Alcohol | 100-51-6 | <20 | TWA: 10ppm 8 hr |
| Polyamine resin | Mixture | <35 | PEL: Not Established |
| Ingredients classified as hazardous/dangerous | | | |

ngredients classified as hazardous/dangerou (Does not contain resinous carcinogens)

4. FIRST AID MEASURES

SKIN CONTACT: Remove from skin using soap and water before curing. Avoid using solvents on skin to remove contamination. Remove

contaminated shoes and clothing. Call a physician if irritation is noted.

EYE CONTACT: Immediately flush eyes with fresh water holding lids apart for 15 minutes, washing within one minute is essential to

achieve maximum effectiveness. Call a physician.

INHALATION: Immediately move to fresh air. If breathing is difficult give oxygen. Call a physician.

INGESTION: Do not induce vomiting. Prevent aspiration (breathing) liquid into lungs. Get medical attention.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water, spray, foam and dry chemical.



Epoxy 314™

RESIN CURING AGENT - YELLOW

MATERIAL SAFETY DATA SHEET - MSDS

DO NOT USE: Flammable materials.

PROTECTIVE EQUIPMENT: Wear full protective equipment including self-contained breathing apparatus.

OTHER: -.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Dispose of as in section 8.

ENVIRONMENTAL PRECAUTIONS: Not applicable.

CLEANING METHOD: Absorb residues with suitable inert absorbent material. Place in container for recovery or

disposal according to local, State or Federal regulations.

7. HANDLING & STORAGE

HANDLING: Impervious gloves should wear long sleeved shirts, coveralls be worn to reduce skin contact.

STORAGE: Store in a cool, dry area in closed containers.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

EXPOSURE LIMITS: Mechanical local exhaust at point of product application if conditions warrant.

RESPIRATORY PROTECTION: Brush or roller application at normal temperatures does not require respiratory protection unless

conducted for extended periods in enclosed spaces with minimal ventilation.

SKIN PROTECTION: Impervious gloves advised, wear long sleeved shirts, coveralls as required preventing skin contact.

EYE PROTECTION: Chemical resistant goggles advised if eye contact possible.

OTHER: --

9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Yellow viscous liquid FLASH POINT: > 200 F TCC

ODOR: Characteristic Mercaptan BOILING POINT: Not applicable

SPECIFIC GRAVITY: 1.11 EXPLOSION LIMITS: Not applicable

% VOLATILE BY VOLUME: 0.5% max VISCOSITY: Honey-like

SOLUBILITY IN WATER: Negligible COLOR: Yellow



Epoxy 314™

RESIN CURING AGENT - YELLOW

MATERIAL SAFETY DATA SHEET - MSDS

VAPOR PRESSURE FREEZING POINT: Not applicable

AND DENSITY: Not applicable

DENSITY AT 20°C: 9.3 lbs/gallon

10. STABILITY & REACTIVITY

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
INCOMPATIBLE MATERIALS: None known

CONDITIONS TO AVOID: Unsupervised mixing with epoxy resins such as WrappFill 811™ epoxy base - white. Expect a

significant exotherm within 5 - 10 minutes at 70 F. This exotherm may generate sufficient heat to be hazardous – avoid severe exotherm or "cook-off" of waste material by pouring over scrap

surfaces in order to eliminate campact masses of material.

HAZARDOUS

DECOMPOSITION PRODUCTS: CO, CO2, unspecified others.

11. TOXICOLOGICAL INFORMATION

SKIN AND EYE CONTACT: Si, irritating, posible sensitizer. INGESTION: Considered slightly toxic.

INHALATION: Overexposure to mist or vapor may cause irritation of respiratory tract – unlikely in normal use at normal

,temperatures.

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Landfill in accordance with local regulations

14. TRANSPORT INFORMATION

IATA, IMO & USDOT: Not Regulated

MAIN RISK: None
SUBSIDIARY RISK: None
UN №: None
CLASS: None
PACKING GROUP: None
PROPER SHIPPING NAME: None

15. REGULATORY INFORMATION

Not available.